

VWF American Oak

VENTED Gas Logs



VWF Split Pine



TPB Blazing Oak



**The Vented Gas
Logs That Heat!**

**VWF American Oak, VWF Split Pine and
TPB Triple Play Gas Logs**



- Blazing Oak Fiber Ceramic logs feature a **TRIPLE PLAY BURNER SYSTEM™** with exclusive triple effect technology producing a full random yellow flame, full depth ember bed and glowing logs
- VWF series available in two log styles - American Oak and Split Pine
- VWF series features innovative and artistically crafted lightweight refractory logs with natural yellow flames
- Built-in ember bed burner maximizes glowing embers and accent flames under logs
- All styles available in three log sizes - 18", 24" and 30"
- Available in manual (VWF Series Only) or millivolt
- Optional safety pilot kits for RADCO models
- CSA design certified models are factory assembled, leak tested for reliability and ease of installation
- UPS shippable




OPTIONS AND SPECIFICATIONS

Product Specifications																
Model CSA	Log Size	Fuel Type	Manual Control				Manual SPK Control				Millivolt				BTU/H	Radiant Heat Output
			Minimum Hearth Area				Minimum Hearth Area				Minimum Hearth Area					
			A	B	C	D	A	B	C	D	A	B	C	D		
VWF18	18"	NG	-	-	-	-	24"	13-1/2"	21"	16"	28"	13-1/2"	25"	16"	60,000	14,000
VWF18	18"	LP	-	-	-	-	24"	13-1/2"	21"	16"	28"	13-1/2"	25"	16"	60,000	14,000
VWF24	24"	NG	-	-	-	-	30"	13-1/2"	27"	16"	34"	13-1/2"	31"	16"	70,000	16,000
VWF24	24"	LP	-	-	-	-	30"	13-1/2"	27"	16"	34"	13-1/2"	31"	16"	60,000	14,000
VWF30	30"	NG	-	-	-	-	36"	13-1/2"	33"	16"	40"	13-1/2"	37"	16"	80,000	18,000
VWF30	30"	LP	-	-	-	-	36"	13-1/2"	33"	16"	40"	13-1/2"	37"	16"	60,000	14,000
RADCO																
VWF18	18"	NG	22"	13"	19"	16"	24"	13-1/2"	21"	16"	28"	13-1/2"	25"	16"	80,000	18,000
VWF18	18"	LP	22"	13"	19"	16"	24"	13-1/2"	21"	16"	28"	13-1/2"	25"	16"	60,000	14,000
VWF24	24"	NG	28"	13"	25"	16"	30"	13-1/2"	27"	16"	34"	13-1/2"	31"	16"	90,000	20,000
VWF24	24"	LP	28"	13"	25"	16"	30"	13-1/2"	27"	16"	34"	13-1/2"	31"	16"	60,000	14,000
VWF30	30"	NG	34"	13"	31"	16"	36"	13-1/2"	33"	16"	40"	13-1/2"	37"	16"	90,000	22,000
VWF30	30"	LP	34"	13"	31"	16"	36"	13-1/2"	33"	16"	40"	13-1/2"	37"	16"	60,000	14,000

Product Specifications							
Model	Log Size	Fuel Type	Millivolt Control				BTU/H
			Minimum Hearth Area				
			A	B	C	D	
18TPB	18"	LP/NG	26"	13"	18"	17"	28,000
24TPB	24"	LP/NG	29"	13"	22-1/4"	17"	38,000
30TPB	30"	LP/NG	33"	13"	25-1/4"	17"	38,000

MINIMUM HEARTH DRAWING



Important:

*The Vented Gas Logs are certified as decorative appliances to the ANSI Z21.60 standard. In independent laboratory testing conducted by a major research university, testing documented the radiant heat output of Martin Hearth & Heating's vented logs utilizing advanced log and burner technology.



A Division of MHS, Inc.
149 Cleveland Drive • Paris, KY 40361
www.martinhearthandheating.com

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice.



OPTIONAL ACCESSORIES



Touch Light™ Table Top/Wall Mount TLM On/Off Remote Control with Receiver.



WMTD - Wireless Wall Switch/Timer with Receiver.



On/Off Hand Held Remote Control with Receiver



On/Off Hand Held Remote Control with 90 min. countdown timer with Receiver and LCD Display



Log Switch with 12" Wire.



Decorative Andiron



Decorative Grate

- Decorative covers for receivers and valves available

Warning:

- Do not operate with glass doors closed, this may cause excessive heat damage to components
- Sunken fireplaces or fireplaces fitted with devices that restrict airflow may result in operational problems.
- The damper stop provided with this unit must be installed to prevent full closure of the fireplace damper.
- It is recommended that a fireplace screen be used during operation of this log set. Always ensure the screen has adequate spaces to allow for the passage of combustion air into the gas log set.
- Keep small children and animals away from the open flame of the gas log set at all times.
- These gas logs are only to be installed in a solid fuel burning fireplace with a working flue constructed of non-combustible materials.

SOLD BY: